

# 26SSA | Solid-Side Single Axle Utility

GVWR: 2,990 lbs  
BED LENGTHS: 8' - 14'  
BED WIDTH: 60" or 77"



**SEALED WIRING HARNESS**  
with molded 4-way flat plug

**FLOOR**  
2" Lumber, installed AFTER painting to ensure no framing is left unfinished. Floor is secured with 5/16" screws and bolt-on board caps.

**TIE DOWNS**  
4 U-bolt

**RAMP GATE**  
48" Bi-Fold Gate offers reduced wind-drag and less obstruction when compared to traditional straight gates. Easy to use and safe.

**SIDES**  
15" Smooth sides

**JACK**  
2000 lb Capacity  
Top-Wind with foot, Bolted-on

**BOXED TAIL LIGHTS**  
Lights are waterproof, rubber-mounted, and the mounting box is raised to the top-rail for increased protection and visibility.

  
**DEXTER AXLE**  
3500 lb E-Z Lube Idler

**TIRES**  
ST205/75D15  
15" x 5 Hole Wheels

**FRAME**  
12 Ga. x 15" Integral Sides

**CROSS MEMBERS**  
3" x 2" x 3/16" Angle

**TONGUE & COUPLER**  
3" Channel Tongue  
2" 5000 lb Capacity A-Frame Coupler



Diamond C uses road-tested DuPont polyurethanes that provide the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice. Some features may be subject availability, delays, or discontinuance.

**Standard Premium Dupont Paint Colors**  
Custom colors available upon request.

