

# 2PSA | All-Purpose, Single Axle Utility

Shown with Optional 48" Bi-Fold Ramp Gate

GVWR: 2,990 lbs  
BED LENGTHS: 8'-14'  
BED WIDTH: 60", 77" or 83"



**BALLED END PIPE TOP-RAIL**  
Permanently sealed, safe, and ergonomic

**BOXED TAIL LIGHTS**  
Lights are waterproof, rubber-mounted, and the mounting box is raised to the top-rail for increased protection and visibility.

## TOP RAIL CHOICES

~ 2-3/8" PIPE with **BALLED ENDS**: Permanently sealed and ergonomic,  
~ 2" x 2" x 1/8" **ANGLE IRON**, or  
~ 2" **SQ. TUBE**



## GATE OPTION

Optional 48" Bi-Fold Gate offers reduced wind-drag and less obstruction when compared to traditional straight gates. Easy to use and safe. (Straight Gate also available)

**JACK**  
2000 lb Top-Wind Jack, with Bolted-on Foot

**DECK**  
2" Treated Lumber

**GRAVEL GUARD**  
Protects fenders from rocks and debris

  
**DEXTER AXLE**  
3500 lb E-Z Lube for quick and easy lubrication

**TIRES**  
ST205/75D15

**WIRING**  
Concealed and protected in the tube framing

**FRAME & CROSS MEMBERS**  
Unique Rectangle Tube Frame and Square Tube Cross-Members provide flush-floor and improved under-carriage ground clearances

**COUPLER**  
2" - 5000 lb Capacity "A-Frame"

**TONGUE**  
3" x 1-1/2" Rectangle Tube

**TIE DOWNS**  
4 - ATV Tie Downs  
1 located in each corner of the trailer

**STAKE POCKETS**  
4 Stake Pockets used as tie down points



Diamond C uses road-tested DuPont polyurethanes that provide the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice. Some features may be subject availability, delays, or discontinuance.

**Standard Premium Dupont Paint Colors**  
Custom colors available upon request.

