


RANGER RU | Tandem Axle Utility

Shown with Optional Flip Jack, and Pipe Top Rail, Slide-In Ramps and Spare Mount

GVWR: 7,000 lbs
BED LENGTHS: 10'-20'
BED WIDTH: 60", 77", or 83"



GATE OPTION

Optional 48" Straight Ramp Gate

FRAME UPGRADE

18' and 20' bed lengths requires 4" channel frame upgrade.

SEALED WIRING HARNESS

with molded 7-way plug

OPTIONAL RAMPS

Side Slide-In Ramps

FLOOR

2" Lumber, installed AFTER painting to ensure no framing is left unfinished. Floor is secured with 5/16" screws and a bolt-on board cap.

TOP RAIL

2" x 2" x 1/8" Angle Iron



JACK

2000 lb Capacity Top-Wind Jack with foot, Bolted-on (shown w/optional Flip-Jack)



DEXTER AXLE

2 - 3500 lb Cambered Axles with 1 Electric Brake

TIRES

ST205/75D15
15" x 5 Hole Wheels

FRAME & CROSS MEMBERS

3" x 2" x 3/16" Angle

STAKE POCKETS

4 Stake Pockets used as tie down points

FULL WRAP TONGUE: 4" Channel

The most vulnerable part of any trailer frame is the midsection in front of the axles. All Diamond C tandem axle trailers have a full-wrap tongue which reinforces the frame all the way to the front fender brace.

COUPLER

2" - 7000 lb Capacity Sleeve-Lock



Diamond C uses road-tested DuPont polyurethanes that provide the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice. Some features may be subject availability, delays, or discontinuance.